

Poolsquad® Pro

Saltwater chlorinator + pH regulator
+ ORP controller

Pool
TECHNOLOGIE

BENEFITS

- **Exclusive Smart Reverse technology:** self-cleaning of the cell according to the hardness of the water without any time adjustment or parameter setting
- **Smart pH:** predictive regulation according to the history for a perfectly stable pH
- **IPS HD panel** for optimal display quality
- **Dynamic backlit capacitive keys** for easy navigation
- **Automatic standby output** by presence sensor
- **Presence sensor** to detect the approach of the user
- **Colour-coded display of the pool status:** blue: optimal water quality, orange: information message, red: alarm
- **Indicators of the status of the device's functions** using pictograms (OFF, STOP, INJ...)
- **Simultaneous display** of setpoints ORP and pH values, salt level and water temperature
- **Low Salt / Normal Salt mode** (depending on model)
- **High quality pH Black and ORP Gold probes**, factory tested and calibrated
- **Bluetooth remote control** with e-Pool® app



 LA FRENCH FAB

FEATURES


- **Smart Power:** current monitoring ensuring stable production
- **Smart Reverse polarity:** the self-cleaning of the cell automatically adapts to the hardness of the water without the need for professional or private intervention
- **Predictive and proportional pH control** in acid (pH-) or basic (pH+) mode according to injection history
- **Chlorine production control by ORP probe**
- **Low mode** to reduce chlorine production, when cover closed or bubbles cover installed
- **Superboost mode:** 125% superchlorination for up to 24 hours to overcome an increased need of disinfectant
- **Automatic winterization and restart from 15°C**
- **Safeties:** lack of water, low salt, cell fault, high and low ORP value, unreacheds setpoints, pH setpoint overrun and overfeeding
- **Multilingual alarm message:** origin of the malfunction indicated by written message
- **Log of events**
- **Self-diagnosis programme for easy maintenance**

Model	Pool volume* (m ³)	Chlorine production (g/h)	Reference	Technical specifications
Poolsquad Pro 8	40	8	ELP023NPSP-G5NM08	Display IPS HD panel
Poolsquad Pro 12	60	12	ELP023NPSP-G5NM12	Screen size 4,3 inches
Poolsquad Pro 16	NS 80 / LS 60	NS 16 / LS 12	ELP023NPSP-G5HX16	Keyboard type capacitive keys
Poolsquad Pro 23	NS 120 / LS 80	NS 23 / LS 16	ELP023NPSP-G5HX23	Presence sensor range (cm) 20
Poolsquad Pro 30	NS 160 / LS 120	NS 30 / LS 23	ELP023NPSP-G5HX30	pH pump flow (l/h) 1,8
Poolsquad Pro 8 panel	40	8	ELP023NPSP-G5NM08 PANORP	Corrective solution pH- or pH+
Poolsquad Pro 12 panel	60	16	ELP023NPSP-G5NM12 PANORP	pH pump type peristaltic
Poolsquad Pro 16 panel	NS 80 / LS 60	NS 16 / LS 12	ELP023NPSP-G5HX16 PANORP	pH regulation type predictive
Poolsquad Pro 23 panel	NS 120 / LS 80	NS 23 / LS 16	ELP023NPSP-G5HX23 PANORP	ORP setpoint adjustment (mV) 200 to 900
Poolsquad Pro 30 panel	NS 160 / LS 120	NS 30 / LS 23	ELP023NPSP-G5HX30 PANORP	Calibration ORP probe 1 point 475 mV

*in hot climates, reduce the volume by 20% - NS : Normal Salt (5 g/l) / LS : Low Salt (1,5 g/l)

INSTALLATION DIAGRAM

Panel mounting




CONTENT

- Control box
- Chlorination cell
- Cell cable (2 m)
- pH Black probe
- Calibration solutions pH 7 & pH 10
- ORP probe Gold
- ORP calibration solution 475 mV
- Saddle clamp x2 (Ø 50 mm)
- Probe holder, injection connector
- ORP probe & ORP measure chamber kit
- Accessories holder with plugs
- Low water/salt/temperature sensor
- Grounding electrode
- Salt and water hardness analysis kit
- Power cable (2 m)
- Collar Ø 63 mm x2
- Reducer Ø 63/50 mm x4
- Wall support (with screws)

OPTIONS

- Independent flow switch
- Empty pH can sensor
- e-Pool® Connect connected Pool kit
- Collar Ø 50 mm x2

WARRANTIES



*See a retailer

